

## RFE RANGE

Digital control with programmer



### Technical features

- ▶ Digital temperature selector for displaying real temperature, set up temperature, clock and other messages.
- ▶ Weekly/daily programmer.
- ▶ Built-in electronic ambient thermostat  $\pm 0,1^{\circ}\text{C}$ .
- ▶ Electronic Triac control optimizer ETCO.
- ▶ Digital adjustable thermometer.
- ▶ Three-level temperature selector: Comfort, Economy and Frost-protection.
- ▶ Flat keyboard for easy cleaning and lockable.
- ▶ Switch On-Off in front side.
- ▶ Choice of two different sizes with ratings from 500 to 2000 W in 580 mm. size and from 750 to 1500 W in 430 mm. size.
- ▶ Thermal safety cut out.
- ▶ Class I insulation.
- ▶ Stylish aluminium body finished in epoxy powder coating RAL 9010.
- ▶ Fitted with mains cable.
- ▶ Safety wall fixing devices to easy the installation.
- ▶ Compatible with wireless energy saver for windows offered as accessory.



MODEL	Short size - 430 mm.									
	RF4E	RF6E	RF8E	RF10E	RF12E	RF14E	RFC7E	RFC9E	RFC11E	RFC14E
Num. of modules	4	6	8	10	12	14	7	9	11	14
Length	cm 41.5	cm 57.5	cm 73.5	cm 89.5	cm 105.5	cm 121.5	cm 66.5	cm 81.5	cm 97.5	cm 121.5
Depth*	cm 10	cm 10	cm 10	cm 10	cm 10	cm 10	cm 10	cm 10	cm 10	cm 10
Height	cm 58	cm 58	cm 58	cm 58	cm 58	cm 58	cm 43	cm 43	cm 43	cm 43
Weight	kg 9.5	kg 13	kg 16.5	kg 20	kg 23.5	kg 27	kg 12	kg 15	kg 17.5	kg 21.5
Input	W 500	W 750	W 1000	W 1250	W 1500	W 2000	W 750	W 1000	W 1250	W 1500
Voltage	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240	V 220-240
Frequency	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60	Hz 50-60
Units per pallet										
- 1300x800	mm	24	24			12				
- 1300x1100	mm									
- 1200x1000	mm	36		24	24		24			24
- 1200x800	mm							24	24	
EAN 13	8432336405105	8432336405204	8432336405303	8432336405402	8432336405501	8432336405709	8432336409400	8432336409509	8432336409608	8432336409707

\*Plus 2cm separated from the wall